

AIR AND GENERAL PURPOSE HOSE

GENERAL PURPOSE

CLEAR REINFORCED PVC (FOOD QUALITY)



APPLICATION:An economical hose for handling air, water, oil, mild chemicals, and alkalis. Clear wall allows visual inspection of product.

COVER:Clear smooth PVC

REINFORCEMENT:Multiple layers of synthetic yarns

TUBE:Clear smooth PVC

TEMPERATURE:-5C to +65C(+25F to +150F)

| Item No | Nom. ID" | Nom. OD" | PSI | Std Pack | Weight# |
|---------------|----------|----------|-----|----------|---------|
| CRPVC-019 | 3/16 | 0.38 | 250 | 300' | 0.05 |
| CRPVC-025 | 1/4 | 0.43 | 250 | 300' | 0.07 |
| CRPVC-025-100 | 1/4 | 0.43 | 250 | 100' | 0.07 |
| CRPVC-031 | 5/16 | 0.53 | 300 | 300' | 0.08 |
| CRPVC-031-100 | 5/16 | 0.53 | 300 | 100' | 0.08 |
| CRPVC-038 | 3/8 | 0.59 | 250 | 300' | 0.09 |
| CRPVC-038-100 | 3/8 | 0.59 | 250 | 100' | 0.09 |
| CRPVC-050 | 1/2 | 0.71 | 250 | 300' | 0.15 |
| CRPVC-050-100 | 1/2 | 0.71 | 250 | 100' | 0.15 |
| CRPVC-063 | 5/8 | 0.87 | 200 | 200' | 0.17 |
| CRPVC-063-100 | 5/8 | 0.87 | 200 | 100' | 0.17 |
| CRPVC-075 | 3/4 | 1.02 | 180 | 200' | 0.23 |
| CRPVC-075-100 | 3/4 | 1.02 | 180 | 100' | 0.23 |
| CRPVC-075-200 | 3/4 | 1.02 | 180 | 200' | 0.23 |
| CRPVC-100 | 1 | 1.30 | 150 | 200' | 0.32 |
| CRPVC-100-100 | 1 | 1.30 | 150 | 100' | 0.32 |
| CRPVC-125 | 1-1/4 | 1.61 | 100 | 100' | 0.58 |
| CRPVC-150 | 1-1/2 | 1.89 | 85 | 100' | 0.69 |
| CRPVC-200 | 2 | 2.44 | 65 | 100' | 1.00 |

Cut Lengths: Plus 10%

Standard Length: 3/16"-3/4" 100'/300' coil, 1" 100'/200' coil, 1-1/4"-2" 100' coil

Product Info: Compliant with the applicable requirements and standards of FDA USDA 3-A and NSF-51. Please specify length when ordering i.e. 100' or 300'

Safety Info: Working pressure ratings are based on 20C (68F). At operating temperature of +65C (150F) reduce working pressure by 50%.

Recommended Couplings: Combination nipples, short shank, brass barbed, cam and groove. All coupling recommendations are to be used as guidelines and are derived from past user preference. In some cases the preferred coupling is of a lesser pressure rating than the hose. Never exceed the working pressure of the lowest rated component in the assembly. If you require further assistance with regards to coupling choice, please contact Harco Ent. customer service at 1-800-361-5361

DISTRIBUTED BY



ENTERPRISES LTD.

1-800-361-5361