## **FOOD HOSE**

## **FOOD - THERMOPLASTIC AND PVC**

## FOODFLEX PVC S&D (FOOD QUALITY)

APPLICATION: For liquid or dry bulk foodstuffs, pharmaceuticals, cosmetics, milk, fruit and vegetable juices, soft drinks, alcoholic beverages, flour, sugar, poulty or meat packing etc. Clear wall allows visual inspection of the product.

COVER:Clear PVC non-marking.
REINFORCEMENT:Clear rigid PVC helix.

TUBE:Smooth clear PVC.

**TEMPERATURE**:-23C to +65C(-10F to +150F)

Item No	Nom. ID"	Nom. OD"	Vacuum	PSI	Bend Radius"	Std Pack	Weight#
FPVC-075	3/4	0.95	29	85	2.00	100'	0.16
FPVC-100	1	1.24	29	80	3.00	100'	0.26
FPVC-125	1-1/4	1.54	29	80	4.00	100'	0.34
FPVC-150	1-1/2	1.81	29	70	5.00	100'	0.44
FPVC-200	2	2.39	29	70	7.00	100'	0.75
FPVC-250	2-1/2	2.94	29	70	8.00	100'	1.10
FPVC-300	3	3.43	29	60	10.00	100'	1.21
FPVC-400	4	4.54	29	50	14.00	100'	2.02

Cut Lengths: Plus 10% Standard Length: 50'/100'

Product Info: Compliant with the applicable requirements and standards of FDA USDA and 3-A

Safety Info: Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

Recommended Couplings: Cam and groove or Sanitary

