

FOOD HOSE

FOOD - THERMOPLASTIC AND PVC

SUPER WIREVAC (FOOD QUALITY)



APPLICATION:An extremely flexible transparent hose for use where full vacuum performance and higher working pressures are required while monitoring the contents of the hose. Ideal for use with most foodstuffs, cosmetics, beverages, and a wide range of chemical solutions. Also suitable for lubricating oils and animal fats.

COVER:Smooth clear PVC

REINFORCEMENT:Spring steel wire helix and plies of polyester yarn

TUBE:Smooth clear PVC

TEMPERATURE:-10C to +65C(15F to +150F)

Item No	Nom. ID"	Nom. OD"	Vacuum	PSI	Bend Radius"	Std Pack	Weight#
WIRES-038	3/8	0.73	28	250	1.20	100'	0.18
WIRES-050	1/2	0.81	28	250	1.50	100'	0.20
WIRES-063	5/8	0.98	28	250	2.00	100'	0.25
WIRES-075	3/4	1.17	28	200	2.40	100'	0.34
WIRES-100	1	1.38	28	200	3.00	100'	0.53
WIRES-125	1-1/4	1.69	28	150	3.70	100'	0.60
WIRES-150	1-1/2	1.97	28	150	4.50	100'	0.78
WIRES-200	2	2.50	28	150	5.50	100'	1.20
WIRES-300	3	3.55	28	100	13.00	100'	2.15

Cut Lengths: Plus 10%

Standard Length: 100'

Product Info: Compliant with the applicable requirements and standards of FDA USDA 3-A NSF-51

Safety Info: Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature. This hose has no fabric reinforcement and normally should not be used under pressure for service at temperatures above 25C (75F).

WIREVAC (FOOD QUALITY)



APPLICATION:An extremely flexible transparent hose for use where full vacuum performance is required while monitoring the contents of the hose. Ideal for use with most foodstuffs, cosmetics, beverages, and a wide range of chemical solutions. Also suitable for lubricating oils and animal fats.

COVER:Smooth clear PVC

REINFORCEMENT:Spring steel wire helix

TUBE:Smooth clear PVC

TEMPERATURE:-10C to +65C(15F to +150F)

Item No	Nom. ID"	Nom. OD"	Vacuum	PSI	Bend Radius"	Std Pack	Weight#
WIRE-025	1/4	0.50	28	110	1.00	100'	0.09
WIRE-038	3/8	0.59	28	250	1.00	300'	0.11
WIRE-050	1/2	0.71	28	250	1.50	300'	0.12
WIRE-063	5/8	0.87	28	200	2.00	200'	0.17
WIRE-075	3/4	1.02	28	180	2.00	200'	0.24
WIRE-100	1	1.30	28	150	3.00	100'	0.35
WIRE-125	1-1/4	1.61	28	100	3.50	100'	0.50
WIRE-150	1-1/2	1.89	28	85	4.00	100'	0.75
WIRE-200	2	2.44	28	65	5.00	100'	1.09
WIRE-300	3	3.50	28	45	12.00	100'	1.84

Cut Lengths: Plus 10%

Standard Length: 100'

Product Info: Compliant with the applicable requirements and standards of FDA USDA 3-A NSF-51

Safety Info: Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature. This hose has no fabric reinforcement and normally should not be used under pressure for service at temperatures above 25C (75F).