

AIR AND GENERAL PURPOSE HOSE

GENERAL PURPOSE

EPDM GENERAL PURPOSE



APPLICATION:Air, water, agricultural spray solutions, and other dilute chemicals Excellent resistance to heat and weathering Also resists animal fats, vegetable oils.

COVER:Smooth red abrasion and weather resistant EPDM synthetic rubber

REINFORCEMENT:Multiple layers of synthetic yarn

TUBE:Synthetic oil mist resistant EPDM synthetic rubber

TEMPERATURE:-30C to +93C(-20F to +200F)

Item No	Nom. ID"	Nom. OD"	PSI	Std Pack	Weight#
GPE-025-150	1/4	0.50	150	300'	0.09
GPE-025-250	1/4	0.55	250	300'	0.13
GPE-031-150	5/16	0.59	150	300'	0.12
GPE-031-250	5/16	0.63	250	300'	0.16
GPE-038-150	3/8	0.68	150	300'	0.15
GPE-038-200	3/8	0.67	200	300'	0.16
GPE-038-250	3/8	0.70	250	300'	0.19
GPE-050-150	1/2	0.81	150	300'	0.20
GPE-050-200	1/2	0.83	200	300'	0.23
GPE-050-250	1/2	0.87	250	300'	0.27
GPE-063-250	5/8	0.98	250	300'	0.31
GPE-075-150	3/4	1.12	150	300'	0.34
GPE-075-250	3/4	1.16	250	300'	0.42
DR-100-200	1	1.42	200	100'	0.64
GPE-100-200	1	1.42	200	300'	0.54
GPE-125-150	1-1/4	1.77	200	100'	0.81
GPE-125-150-100	1-1/4	1.77	200	100'	0.60
GPE-150-150	1-1/2	2.00	200	100'	0.95
GPE-150-150-100	1-1/2	2.01	200	100'	0.74
GPE-200-150-100	2	2.52	150	100'	0.91
GPE-200-150	2	2.50	200	100'	1.13

Cut Lengths: Plus 5%

Standard Length: 1/4"- 1" 50'/100'/300' reels approx, 1-1/4" - 1-1/2" 50'/300' reels approx, 2" 50'/100'/300' reels approx

Recommended Couplings: High Pressure 1" to 1-1/2" for air service if the working pressure exceeds 150 psi. High Pressure, Short shank, universal, or Combination nipples all other sizes. Crimplok universals. All coupling recommendations are to be used as guidelines and are derived from past user preference. In some cases the preferred coupling is of a lesser pressure rating than the hose. Never exceed the working pressure of the lowest rated component in the assembly. If you require further assistance with regards to coupling choice, please contact Harco Ent. customer service at 1-800-361-5361

EPDM GENERAL PURPOSE 300



APPLICATION:Air, water, agricultural spray solutions, and other dilute chemicals Excellent resistance to heat and weathering Also resists animal fats, vegetable oils.

COVER:Smooth red abrasion and weather resistant EPDM synthetic rubber

REINFORCEMENT:Multiple layers of synthetic yarn

TUBE:Synthetic oil mist resistant EPDM synthetic rubber

TEMPERATURE:-30C to +93C(-20F to +200F)

Item No	Nom. ID"	Nom. OD"	PSI	Std Pack	Weight#
GPE-025-300	1/4	0.55	300	300'	0.14
GPE-038-300	3/8	0.70	300	300'	0.20
GPE-050-300	1/2	0.87	300	300'	0.27
GPE-075-300	3/4	1.16	300	300'	0.44
GPE-100-300	1	1.42	300	300'	0.59

Cut Lengths: Plus 5%

Standard Length: 300'

Recommended Couplings: High Pressure, Short shank, universal, or Combination nipples all other sizes. All coupling recommendations are to be used as guidelines and are derived from past user preference. In some cases the preferred coupling is of a lesser pressure rating than the hose. Never exceed the working pressure of the lowest rated component in the assembly. If you require further assistance with regards to coupling choice, please contact Harco Ent. customer service at 1-800-361-5361