

# PETROLEUM STEAM AND CHEMICAL HOSE

## STEAM

### STEAM 250



**APPLICATION:**An extremely flexible hose for use with saturated steam at pressures to 250 PSI .

**COVER:**Red abrasion and heat resistant EPDM rubber, with embossed brand and pressure.

**REINFORCEMENT:**Multiple layers of high tensile steel cords.

**TUBE:**Black heat resistant EPDM synthetic rubber.

**TEMPERATURE:**-40C to +210C(-40F to +406F)

Item No	Nom. ID"	Nom. OD"	PSI	Std Pack	Weight#
ST250-050-50	1/2	0.98	250	50'	0.32
ST250-050-100	1/2	0.98	250	100'	0.32
ST250-075-50	3/4	1.26	250	50'	0.48
ST250-075-100	3/4	1.26	250	100'	0.48
ST250-100-50	1	1.50	250	50'	0.60
ST250-100-100	1	1.50	250	100'	0.60
ST250-125-50	1-1/4	1.81	250	50'	0.80
ST250-125-100	1-1/4	1.81	250	100'	0.80
ST250-150-50	1-1/2	2.13	250	50'	1.10
ST250-150-100	1-1/2	2.13	250	100'	1.10
ST250-200-50	2	2.64	250	50'	1.48
ST250-200-100	2	2.64	250	100'	1.48
ST250-250	2-1/2	3.22	250	100'	2.00
ST250-300	3	3.78	250	100'	3.40

**Cut Lengths:** Plus 10%

**Standard Length:** 50'/100'

**Product Info:** Longer lengths available on request. Please check for availability and pricing

**Recommended Couplings:** High Pressure with interlocking clamps

### STEAM 250 ASSEMBLY

Item No	Assembly Description	Weight#
ST250-075-FFNS	3/4"X50'STEAM250 C/W HP F/F NO SPUD	30.02
ST250-075-HPASS	3/4"X50'STEAM 250 M+F HP 1 SPUD	27.61
ST250-075-HPFF	3/4"X50'STEAM250 C/W HP F/F 2 SPUDS	29.02
ST250-100-HPASS	1"X50'STEAM 250 M+F HP 1 SPUD	34.64
ST250-150-HPASS	1-1/2"X50' STEAM 250 C/W M+F H.P.	64.90
ST250-200-HPASS	2"X50' STEAM 250 C/W M+F H.P.	87.80